

## Exxon Gasolines - Reformulated Gasoline



### Product Description

Dedicated to enhance your life on the move, Exxon high-quality fuels are sold worldwide to provide you with the reliable and trusted fuels you've come to expect. Exxon gasolines are specially formulated for each market in which Exxon fuels are sold - including yours.

Exxon quality gasolines are available in three octane grades. All Exxon gasolines provide power, easy startup and help minimize emissions in your vehicles.

Gasolines blended for today's engines are required to:

- Provide energy for power
- Form a combustible mixture
- Ignite readily
- Burn smoothly
- Minimize harmful emissions
- Protect the fuel delivery system

And whenever you fill up at an Exxon service station, you can feel confident that Exxon gasolines will do everything they should do for your vehicle. We have developed three quality gasolines that will perform to the high standards you've come to expect.

Exxon Regular Unleaded - Our most popular gasoline has an octane level of 87 in most areas and is blended with a detergency package that helps keep your vehicle's fuel injectors and intake valves clean when used regularly.

Exxon Plus - With an octane level of 89 in most areas, this gasoline was developed to meet the needs of drivers like you with vehicles that can benefit from a fuel with a higher octane.

Exxon Supreme - Formulated to meet the demands of today's engines, it generally has an octane level of 93, but is blended with an octane level of 91 on the West Coast and in some other geographic locations.

You can find out what octane your vehicle's engine needs by checking your owner's manual.

You can be sure Exxon gasolines meet all applicable regulatory standards and ASTM D 4814 in the US. And we go the extra mile by testing them at key points along the way to the service station so the gas you put in your vehicle will work unflinchingly.

Committed to Excellence

Providing you and your vehicle with a high-quality fuel takes more than technical leadership. Quality must first be designed into the fuel. After that, the fuel must be refined and blended properly, and then must be guarded against contamination as it moves through the distribution system. To help ensure your driving satisfaction, we have stringent quality control procedures to help protect Exxon fuels at every step of the process.

You can fill up your vehicle with confidence, knowing that we are also one of the few oil companies in the U.S. that maintains an active research organization dedicated to keeping the gasoline that goes into your vehicle in step with the latest vehicle testing technology. We're always on the lookout for anything that might give Exxon gasolines an extra "edge" for you.

We are committed to providing the highest quality of gasoline for your vehicle. If you have a problem with your vehicle that is related to the quality of our products, we invite you to call our Customer Assistance Center at 1-800-662-4592. Even if you want to ask a question or share a comment about our products or services, feel free to give us a call.

### Health & Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDSs are available via the Internet at ExxonMobil.com. This product should not be used for purposes other than its intended use.

#### MAIN HAZARD: FIRE

Keep away from ignition sources.

Discharge your static electricity before fueling.

Fill portable containers on the ground.

Handle/Transport in closed or properly vented containers and systems, consistent with all applicable laws.

Harmful or fatal if swallowed.

Avoid breathing the vapors and skin contact.

Do not wash down spills with water. Prevent all spills from reaching water.

### Product Properties

Exxon Gasolines - Specifications	Exxon Supreme	Exxon Plus	Exxon Regular
Octane, (R+M)/2	93.0	89.0	87.0
Copper Corrosion, 3hr @ 122°F, Rating, Rating	No. 1 Max.	No. 1 Max.	No. 1 Max.
Sulfur Content, Wt. %	0.05 Max.	0.05 Max.	0.05 Max.
Lead Content, gPb/gal	.05 Max.	.05 Max.	.05 Max.
Oxidation Stability, Minutes	240 Min.	240 Min.	240 Min.
Benzene Content, Wt. %	1.30 Max.	1.30 Max.	1.30 Max.
Existent Gum, mg/100 mL	5 Max.	5 Max.	5 Max.
Oxygen Content, Wt. %	1.5 - 4.0	1.5 - 4.0	1.5 - 4.0
Volatility	Seasonal	Seasonal	Seasonal
VOC Reduction, %	21.4 - 23.4 Min.	21.4 - 23.4 Min.	21.4 - 23.4 Min.
RVP, psi	6.4 - 15.0 Max.	6.4 - 15.0 Max.	6.4 - 15.0 Max.
Distillation, °F Max.			
10%	122 - 158	122 - 158	122 - 158
50%	230 - 250	230 - 250	230 - 250
90%	365 - 374	365 - 374	365 - 374
End Point	437	437	437
T(V/L=20), °F Min.	105 - 124	105 - 124	105 - 124

#### Specifications

All Exxon Gasolines meet the following industry specifications:	
ASTM D 4814	

ExxonMobil Fuels Marketing  
3225 Gallows Rd.  
Fairfax, VA 22037

800 662-4592

Due to continual product research and development, the information contained herein is subject to change without notification. Typical properties may vary slightly.

© 2001 Exxon Mobil Corporation. All rights reserved.

